

Dryer



Our efficient drying unit allows the bike to dry quickly after the cleaning process. Air flows out of 5 radial fans with high volume and low pressure over the bike. All areas of the bike can be comfortably reached from below and from the side while passing through.

The drying unit is compatible with all of our products: mini duo, duo & UNO Station.

Technical specifications

Power consumption	1.5 kW
Supply voltage	230 V
Rated speed:	2870/3450 U/min.
Motor protection class:	IP 54
Max. Volume flow:	70 m ³ /min.
Max. Total pressure increase:	900 Pa
Other	<ul style="list-style-type: none">• Control cabinet - IP56 Splash-/Dustproof according to VDE and CE standard with plug-in installation• Wheel turning unit for an excellent drying of the wheels (rim and tire)• cashless payment with touch display for self-service (optional)



Compressors



High performance blade-compressor

Technical specifications

High-performance blade-compressor
for heavy use in the UNO station, not only for pre-cleaning, but also for manual main wash.

Power consumption	2.2 kW
Supply voltage	230 V
Pressure	10 bar
Air performance	240 l/min.
Noise emission	62 – 73 dB (A)
Rotation	1.450 rpm (50 Hz) – 1.760 rpm (60 Hz)

- Other**
- Continuous run or start/stop
 - Less than 3 ppm oil carryover
 - Integral oil cooler



Mobile Compressor

Technical specifications

Mobile Compressor

Our powerful and compact air compressor with two connections for comfortable working with different tools.

Power consumption	1.6 kW
Supply voltage	230 V
Pressure	5 – 8 bar
Air performance	170 l/min.
Noise emission	48 – 65 dB (A)
Rotation	1.450 rpm
Weight	31.5 kg
Dimensions	75 x 68 x 29,5 cm (L x H x W)

Änderungen vorbehalten